

GHK-15OPNA

FEATURES

- SVGA (1024 x 768) (250 cd/m2)
- VGA & DVI Signal Input
- OSD Control on the Back Side
- DC 12V Power Input
- Integrated Industry-Standard Design
- Support Embedded Mounting



RoHS



15 inch
TFT

WT

OEM
ODM

PRODUCT SPECIFICATIONS

LCD	
Panel Type	AU LCD Panel (Optional)
Resolution (pixel)	1024*768
Display Area (mm)	304.128(H)x228.096(V)
Brightness (nit)	250nit /350nit /550nit (Optional)
Contrast Ratio	700:1
Colors	16.2M
View Angle (U/D/L/R)	70/60/80/80
Backlight Lifetime	50000hrs
OSD Control	Auto Menu Select (+,-) Exit On/Off
Touch Screen	
Type	NO(Optional)
Resolution(pixel)	NO
Transmittance	NO
Interface	
Signal Input	VGA+DVI (15 Pin D-sub/DVI-D Connector) AV Input / Video Input /Audio Input (Optional)
Touch Connectors	USB / RS232(Optional)
Power	
Power Input	DC-in 12V=4A (50~61HZ)-DC Jack (2.0mm) & 3-PIN Industrial Connectors
Power Consumption	≤48W
Mechanical	
Material	High Strength Cold Rolling Steel Chassis
Mounting	Support Embedded Mounting
Dimensions	357.3(H) x 292.0(V) x 42.8(D)
Environment	
Operating Temp	-30~85C°
Storage Temp	-30~85C°
Relative Humidity	10~90% @40C° Non-condensing without touch screen
Vibration	1G peak,5~500Hz(Random)
Shock	15G peak acceleration (11msec.duration)
Rating	Facilitate installation of the demolition, solid portfolio
Ordering Information	
GHK-15OP-NA	15"Open Frame Monitor with VGA/DVI input and power adapter (250nit)
GHK-15OP-TA	15"Open Frame Touch Monitor with 5wire resistive touch screen,VGA/DVI input (350nit)

DIMENSIONS

