

## GHK-21OP-NB

### FEATURES

- SVGA (1920 x 1080) (250 cd/m2)
- VGA & DVI Signal Input
- OSD Control on the Back Side
- DC 12V Power Input
- Integrated Industry-Standard Design
- Support Embedded Mounting



RoHS



21 inch  
TFT



OEM  
ODM

### PRODUCT SPECIFICATIONS

LCD	
Panel Type	LCD Panel (Optional)
Resolution (pixel)	1920*1080
Display Area (mm)	476.64(H)x268.11(V)
Brightness (nit)	250nit (Optional)
Contrast Ratio	1000:1
Colors	16.7M
View Angle (U/D/L/R)	80/80/85/85
Backlight Lifetime	30000hrs
OSD Control	Auto Menu Select (+,-) Exit On/Off
Touch Screen	
Type	NO(Optional)
Resolution(pixel)	NO
Transmittance	NO
Interface	
Signal Input	VGA+DVI ( 15 Pin D-sub/DVI-D Connector ) AV Input / Video Input /Audio Input (Optional)
Touch Connectors	NO
Power	
Power Input	DC-in 12V=4A (50~61HZ)-DC Jack (2.0mm) & 3-PIN Industrial Connectors
Power Consumption	≤48W
Mechanical	
Material	High Strength Cold Rolling Steel Chassis
Mounting	Support Embedded Mounting
Dimensions	534.5(H) x 309(V) x 41.4(D)
Environment	
Operating Temp	-25~80C°
Storage Temp	-30~80C°
Relative Humidity	10~90% @40C° Non-condensing without touch screen
Vibration	1G peak,5~500Hz(Random)
Shock	15G peak acceleration (11msec.duration)
Rating	Facilitate installation of the demolition, solid portfolio
Ordering Information	
GHK-21OP-NB	21"Open Frame Monitor with VGA/DVI input and power adapter (250nit)
GHK-21OP-TB	21"Open Frame Touch Monitor with Infrared touch screen,VGA/DVI input (250nit)

### DIMENSIONS

